

Characteristics and use of products

○ round plastic rings PEHD and PP-C are used in a wide range inter alia, systems, plumbing, construction, industry, agriculture, etc.

○ The basic dimensions:

- D-diameter 1000mm, the height h-500mm, wall thickness s-15mm
- D-diameter 1200mm, the height h-500mm, wall thickness s-16mm

Application

○ The depicted item is widely used in various construction-type circular drainage wells, water meter, lymph pumping tanks, etc. with an inside diameter of 1000 mm and 1200mm.

○ The tanks with a depth (height levels) max. 5500 mm, can be embedded on the ground level, loosely placed on a rigid carrier substrate. They can also be recessed into the ground level and used as a manhole, the water tank with the same depth.

○ Because of the properties and resistance of the material - plastic tanks of this type can be used for storage of chemically aggressive solutions, solids, etc.

○ from the rings can also be prepared resistant trough in terms of chemical, or pipelines.

Advantages:

○ Long-term climate and chemical resistance

○ a broad range of diverse applications

○ A very precise output by pressure injection

○ The easy way to connect with key, simple welding of components for assembly (available in the permanent offer: wire, plate, castings grades of the same material)

○ Easy workability

AMARGO

tel: +48 22 758 88 27 +48 22 244 29 38 +48 22 201 24 03 fax: +48 22 758 88 27

biuro@amargo.pl www.amargo.pl ul. Pogodna 10 Piotrkówek Mały, 05-850 Ożarów Mazowiecki
NIP: 723-152-09-67 Regon: 140030426